Air King Ventilation Products®

SPECIFICATIONS

AKLC

EXHAUST FAN WITH LIGHT

70 CFM/2.5 SONES @ 0.10" WG. -HVI CERTIFIED
120 Volts, 1.6 amps, 60 hz.

- **Grill**
  AKLC701 - Oil Rubbed Bronze Finish: 13 1/2" diameter.
  AKLC702 - Nickel Finish: 13 1/2" diameter.
  AKLC703 - White Finish: 13 1/2" diameter.
- **Light Lens**
  Ribbed frosted glass light lens.
- **Light Housing**
  Heavy gauge cold rolled steel c/w baked enamel finish; locks in place on the grill via two integral tabs.
- **Blower Wheel**
  One piece polymeric wheel, 4 1/2" diameter, 1" wide, with 10 fins.
- **Motor**
  Single coil plug-in, two pole motor, life time lubrication, thermally protected. Rated 120 volts, 60 hz., 1.6 amps.
- **Fan Housing**
  23 ga. Galvanized metal housing, dimensions 8" x 6 7/8" x 5 1/2", double metal thickness mounting tabs.
- **Duct Collar**
  Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.
- **Lighting**
  2 - 60 watt maximum light capacity (bulbs not included).



CUL/HVI

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

- **Unit Mounting**
  Rated Type **IC** for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit will mounts directly to the joist with a rough in opening of 8 3/16" x 7 1/16". The housing will mount through drywall thickness up to 3/4".
- **Ventilating Area**
  For bathrooms up to 70 sq. ft. for other rooms up to 85 sq. ft.
- **Single Pack Shipping Info**
  Box Dim: 11 1/2" x 13 1/4" x 9 1/2"
  AKLC701 - UPC: 0-8316228711-3
  AKLC702 - UPC: 0-8316228721-2
  AKLC703 - UPC: 0-8316228731-1

PERFORMANCE

	Static Pressure (inches of w.g.)								*HVI Sones @ .1 SP*	*Fan Speed RPM*	*Power Watts*
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3			
Air Flow - CFM	81	75	70	67	64	58	50	42	2.5	1375	33

PROJECT		ARCHITECT	
LOCATION		ENGINEER	
CONTRACTOR		SUBMITTED BY	DATE

FAN NUMBER	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS

c UL us

2100 HVI CERTIFIED™

U.S.: 820 Lincoln Drive
West Chester, Pennsylvania 19380-4466
Tel: (610) 692-7400 • 877-304-3785
Fax: (610) 696-8048

Canada: 110 Glidden Road
Brampton, Ontario L6T 2J3
Tel: (905) 456-2033
Fax: (905) 456-1015

Downloaded from www.Manualslib.com manuals search engine